

## Type SDD Manual Tong



The type SDD manual tong is designed for make-up and break-up of pipe connections with torque capacity up to 100,000 lbs/ft. It can handle OD size from 4-1/2" to 17" by changing out of lug jaw and hinge jaw. The products are designed and manufactured in accordance to API Spec 7K.

## Type DB Manual Tong



The type DB manual tong is designed for make-up and break-up of pipe connections with torque capacity up to 65,000 lbs/ft. It can handle OD size from 3-1/2" to 17" by changing out of lug jaw and hinge jaw. The products are designed and manufactured in accordance to API Spec 7K.

## Type B Manual Tong



The type B manual tong is designed for make-up and break-up of pipe connections with torque capacity up to 55,000 lbs/ft. It can handle OD size from 3-1/2" to 13-3/8" by changing out of lug jaw. This tong can be extended to handle from 13-3/8" OD - 36" OD casing by using casing head assembly with torque capacity of 50,000 lbs/ft. The products are designed and manufactured in accordance to API Spec 7K.

## **Type C Manual Tong**



The type C manual tong is designed for make-up and break-up of pipe connections with torque capacity up to 35,000 lbs/ft. It can handle OD size from 2-3/8" to 10-3/4" by changing out of lug jaw and short jaw. The products are designed and manufactured in accordance to API Spec 7K.

## **Type LF Manual Tong**



The type LF manual tong is designed for make-up and break-up of pipe connections with torque capacity up to 16,000 lbs/ft. It can handle OD size from 2-3/8" to 7" by changing out of lug jaw. The products are designed and manufactured in accordance to API Spec 7K.